

DPO70E Series Optical Probes

DPO70E1 and DPO70E2



Features and benefits

- Accurate Optical Reference Receiver (ORR) filters for 25 GBd, 26 GBd, 28 GBd, and 53 GBd optical networking standards ensure highest measurement accuracy and correlation
- Versatile design delivers Bessel-Thompson ORR specified bandwidths or unfiltered response up to 59 GHz on multiple channels
- Broad wavelength with FC/PC or FC/APC connector options
- High sensitivity and low noise provide best SNR for high-speed signal analysis
- Enables deep analysis of PAM4 and PAM2 (NRZ) signaling, equalization and error detection/isolation
- Compatible with ATI and TekConnect[®] channels for maximum performance or channel density

Applications

- Datacenter networking equipment design validation
- Research - Characterization of laser-based velocity measurement system (e.g. PDV, BLR) and other optical phenomena
- System debug of optical interfaces using a real time oscilloscope's unique debug features

The DPO70E Series Optical probes can be used as Optical Reference Receivers (ORR) for high speed serial data signals (using selectable Bessel-Thomson ORR filters), or can be used as a conventional O/E converter for general wide-bandwidth optical signal acquisition. The DPO70E Series is compatible with DPO/MSO70000 C/DX/SX models. Connect to TekConnect channels for up to 33 GHz electrical bandwidth. Connected to ATI channels, the DPO70E1 provides up to 42 GHz electrical response; the DPO70E2 provides up to 59 GHz electrical bandwidth response.


Optical reference receiver performance

Achieving Optical Reference Receiver (ORR) response requires sufficient instrument bandwidth to ensure smooth frequency roll-off characteristics beyond the data rate. For design of Datacenter Networking equipment, an ORR with a fourth-order Bessel-Thomson (BT4) frequency response is generally used. For NRZ (PAM2), the reference receiver's -3 dB electrical bandwidth is set to a frequency of 75% of the optical symbol rate and its bandwidth limit guard bands are specified to a frequency of 150% of the optical symbol rate. Using these values for a 28 Gbd optical signal yields the following frequency response requirements:

Optical reference receiver attenuation	Frequency
-3 dB	$0.75 * 28 \text{ G} = 21 \text{ GHz}$
Nominal: -13.4 dB Range: -9.4 to -17.4 dB	$1.50 * 28 \text{ G} = 42 \text{ GHz}$

For PAM4 signals the BT4 filter is tuned lower. The electrical bandwidth is set to a frequency corresponding to 50% of the symbol rate. The ORR BT4 filters for the important symbol rates of PAM4 standards, such as 53.152 GBd and 26.5625 GBd, are also available in the DPO70E Series.

Acquiring signals on a high-bandwidth ATI channel maintains linear phase across the passband of the channel. This makes it possible to enable true optical reference receiver (ORR) quality filters for baud rates up to 28 Gbd on the DPO70E1, which requires a controlled electrical response up to 42 GHz, and PAM4 baud rates up to 53 GBps on the DPO70E2. The graph below shows a typical frequency response of the DPO70E1 on a DPO77002SX real-time oscilloscope.



Fourth order Bessel-Thompson frequency response of the DPO70E1 Optical Probe and DPO70000SX ATI channel

The smooth, controlled system response with the DPO70E Series and DPO70000SX oscilloscope is possible because the oscilloscope's system software calculates the BT4 filters using the S-parameters unique to the optical probe and the oscilloscope channel. Most real-time oscilloscopes today have a rather sharp roll-off (e.g. "brick wall") at or just above the rated channel bandwidth. This response limits the ability to replicate a true BT4 response, which has a much more gradual roll-off characteristic. Without a true BT4 response, the signal's eye opening will be reduced, adversely impacting the accuracy of the measurement.


Optical signal analysis

The DPO70E Series optical probe enables deep analysis of PAM4-O and PAM2 (NRZ) signaling using Tektronix' industry leading DPOJET Jitter and Eye Analysis and PAM4 Analysis software.

DPOJET supports the traditional optical measurements. These measurements include extinction ratio, eye high, eye low, eye crossing, and optical modulation amplitude.

Industry-leading PAM4 signaling analysis

The PAM4-O software supports analysis of PAM4 optical signals with clock recovery, error detection, and IEEE and OIF-CEI standard specific measurements, e.g. TDECQ.




PAM4 Analysis Software with Eye Diagram and Example measurement Results

Versatile configurations

The versatile design of the DPO70E Series optical probe is compatible with either a DPO70000SX oscilloscope's ATI channel or channels with the TekConnect interface. This versatility makes the DPO70E Series optical probe suitable for use with all DPO70000SX, MSO/DPO70000DX, and MSO/DPO70000C series oscilloscopes.



Optical Reference Receiver with controlled response up to 59 GHz on a DPO70000SX oscilloscope's ATI channel



DPO70E series probes are compatible with MSO/DPO70000DX models



DPO70000SX models support up to 4 optical inputs with 33 GHz maximum bandwidth

Specifications

All specifications are guaranteed unless noted otherwise. All specifications apply to all models unless noted otherwise. ¹

Nominal characteristics

Electrical bandwidth (-3 dB) ²	DPO70E1: 33 GHz DPO70E2: 59 GHz
4th order Bessel Thomson filters ³	User specified
Coupling	DC
Wavelength range (Opt. FC/PC)	DPO70E1: 750 nm to 1650 nm DPO70E1: 850 nm, 1310 nm, 1550 nm (calibrated) ⁴ DPO70E2: 1200 nm to 1650 nm DPO70E2: 1310 nm, 1550 nm (calibrated) ⁴
Wavelength range (Opt. FC/APC)	1310 nm, 1550 nm (calibrated) ⁴ DPO70E1: 1260 nm to 1650 nm DPO70E2: 1200 nm to 1650 nm

Optical connector types

Opt. FC/PC	FC/PC (FC is determined by the changeable JAE connector)
Opt. FC/APC	FC/APC

Input fiber core diameter (maximum)

Probe	Option	Specification
DPO70E1	FC/PC	50 μm (SMF and MMF compatible)
	FC/APC	9 μm (SMF compatible)
DPO70E2	FC/PC	9 μm (SMF compatible)
	FC/APC	

Oscilloscope interfaces	ATI (1.85 mm RF connector), TekConnect
--------------------------------	--

¹ Unless otherwise specified, all optical specifications tested at 1310 nm and 1550 nm. Also tested at 850 nm for the DPO70E1.

² With DSP.

³ Filters are optical reference receiver compliant below 22 GHz electrical bandwidth for DPO70E1, and 29.5 GHz electrical bandwidth for DPO70E2.

⁴ The DPO70E Series supports a calibrated amplitude response at custom wavelengths after a user calibration procedure is run.

Optical characteristics

Rise time (10% to 90%)⁵	DPO70E1: 10.2 ps, typical DPO70E2: 7.5 ps, typical
Maximum input power (linear response)	DPO70E1: 4 mW, typical DPO70E2: 2 mW, typical
Maximum non-destruct input signal	DPO70E1: 8 mW, typical DPO70E2: 4 mW, typical
Input return loss	DPO70E1: >19 dB, typical DPO70E2: >27 dB, typical
Aberrations	3% pk-pk (for ORR filters only), typical
Output zero (dark level) (for filters >25 GHz bandwidth)	± (10 μW + 4% * vertical offset), 1310 nm and 1550 nm ± (12 μW + 4% * vertical offset), 850 nm (DPO70E1 only)
Polarization dependence	DPO70E1 (1310 nm and 1550 nm inputs): ± 0.3 dB maximum DPO70E2 (1310 nm and 1550 nm inputs): ± 0.2 dB maximum
DC vertical accuracy	± (25 μW + [(0.04 + Connector Uncertainty) * ((vertical reading) - (vertical offset))]), typical

⁵ With flat to max filter on ATI channel.

Optical characteristics

DPO70E1: Optical noise, RMS 850 nm

Filter	TekConnect		ATI	
	Typical (μW)	Max (μW)	Typical (μW)	Max (μW)
Unfiltered O/E response	13.51	17.62	17.92	19.40
Flat to max	20.05	27.90	35.66	38.40
User 12.6 GHz (for 16.8 GBd NRZ)	12.09	15.64	11.61	16.35
User 21.0375 GHz (for 28.05 GBd NRZ)	12.94	18.40	13.66	19.30

1310 nm

Filter	TekConnect		ATI	
	Typical (μW)	Max (μW)	Typical (μW)	Max (μW)
Unfiltered O/E response	7.98	9.53	10.01	10.77
Flat to max	11.40	13.72	16.19	24.20
User 12.6 GHz (for 16.8 GBd NRZ)	5.59	8.25	6.70	8.87
User 21.0375 GHz (for 28.05 GBd NRZ)	7.47	9.70	7.88	10.44

1550 nm

Filter	TekConnect		ATI	
	Typical (μW)	Max (μW)	Typical (μW)	Max (μW)
Unfiltered O/E response	8.15	10.08	10.65	11.44
Flat to max	11.74	14.66	16.64	25.60
User 12.6 GHz (for 16.8 GBd NRZ)	5.91	7.87	6.94	9.27
User 21.0375 GHz (for 28.05 GBd NRZ)	7.58	9.23	8.15	10.89

DPO70E2: Optical noise, RMS 1310 nm

Filter	TekConnect		ATI	
	Typical (μW)	Max (μW)	Typical (μW)	Max (μW)
Unfiltered O/E response	11.8	13.8	16.8	18.8
Flat to max	11.8	13.8	16.8	18.8
User 12.6 GHz (for 16.8 GBd NRZ)	8.3	10.3	8.3	10.3
User 29.5 GHz	NA	NA	12.5	15.3

1550 nm

Filter	TekConnect		ATI	
	Typical (μW)	Max (μW)	Typical (μW)	Max (μW)
Unfiltered O/E response	13.8	15.8	18.8	20.8
Flat to max	13.3	15.3	19.3	21.3
User 12.6 GHz (for 16.8 GBd NRZ)	9.3	11.3	9.3	11.3
User 29.5 GHz	NA	NA	14	16.8

Compatibility

Compatible Tektronix oscilloscopes DPO70000SX, DSA/DPO70000D, MSO/DPO70000DX, MSO/DSA/DPO70000C

Temperature

Temperature
Operating 10 °C to +40 °C
Non-operating -22 °C to +60 °C

Ordering information

Models

DPO70E1	33 GHz bandwidth, single/multi-mode, 750 nm to 1650 nm, optical probe for MSO/DPO70000 Real Time Oscilloscopes
DPO70E2	59 GHz bandwidth, single-mode 1200 nm to 1650 nm, optical probe for MSO/DPO70000 Real Time Oscilloscopes

Standard accessories

Hard case, Instruction manual, Certificate of Traceable Calibration, One year warranty, Optical fiber cleaning tool, ATI input support accessory



Recommended oscilloscope application software

PAM4-O	Optical Measurements for PAM4
DJA	DPOJET Jitter and Eye Diagram Analysis with Optical Measurements
DJAN	DPOJET Jitter and Eye Diagram Analysis with Vertical Noise Separation
SDLA	Serial Data Link Analysis

Recommended accessories

006-8327-xx	Optical connector cleaner
-------------	---------------------------

Options

Product options

Note: Select an optical input connector type from the following mandatory, mutually exclusive options.

- FC/APC** FC/APC optical input connector (typically used in research applications)
- FC/PC** FC/PC optical input connector (typically used in networking/data center network applications)

Service options

- Opt. C3** Calibration Service 3 Years
- Opt. C5** Calibration Service 5 Years
- Opt. D3** Calibration Data Report 3 Years (with Opt. C3)
- Opt. D5** Calibration Data Report 5 Years (with Opt. C5)
- Opt. G3** Complete Care 3 Years (includes loaner, scheduled calibration, and more)
- Opt. G5** Complete Care 5 Years (includes loaner, scheduled calibration, and more)
- Opt. R3** Repair Service 3 Years (including warranty)
- Opt. R5** Repair Service 5 Years (including warranty)

Probes and accessories are not covered by the oscilloscope warranty and service offerings.



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

ASEAN / Australasia (65) 6356 3900
Belgium 00800 2255 4835*
Central East Europe and the Baltics +41 52 675 3777
Finland +41 52 675 3777
Hong Kong 400 820 5835
Japan 81 (3) 6714 3086
Middle East, Asia, and North Africa +41 52 675 3777
People's Republic of China 400 820 5835
Republic of Korea +822 6917 5084, 822 6917 5080
Spain 00800 2255 4835*
Taiwan 886 (2) 2656 6688

Austria 00800 2255 4835*
Brazil +55 (11) 3759 7627
Central Europe & Greece +41 52 675 3777
France 00800 2255 4835*
India 000 800 650 1835
Luxembourg +41 52 675 3777
The Netherlands 00800 2255 4835*
Poland +41 52 675 3777
Russia & CIS +7 (495) 6647564
Sweden 00800 2255 4835*
United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
Canada 1 800 833 9200
Denmark +45 80 88 1401
Germany 00800 2255 4835*
Italy 00800 2255 4835*
Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
Norway 800 16098
Portugal 80 08 12370
South Africa +41 52 675 3777
Switzerland 00800 2255 4835*
USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tek.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.



12 Sep 2018 55W-61281-3

www.tek.com

Tektronix[®]

