
USRP-2945

2024-11-25



Contents

USRP-2945 Specifications..... 3

USRP-2945 Specifications

Definitions

Warranted specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

Characteristics describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- **Typical** specifications describe the expected performance met by a majority of the models.
- **Nominal** specifications describe parameters and attributes that may be useful in operation.

Conditions

Specifications are valid at 25 °C unless otherwise noted.

Receiver

Number of channels	4
Frequency range	10 MHz to 6 GHz
Frequency step	<1 kHz
Gain range ^[1]	0 dB to 95 dB

Gain step	1 dB
Maximum input power (P_{in})	+10 dBm
Frequency accuracy ^[2]	2.5 ppm
Maximum instantaneous real-time bandwidth ^[3]	80 MHz
Maximum I/Q sample rate	100 MS/s
Analog-to-digital converter (ADC)	
Resolution	14 bit
sFDR	88 dB

Table 1. Noise Figure

Frequency	Noise Figure ^[4] (dB)
10 MHz to 3 GHz	<5
3 GHz to 5 GHz	<4
5 GHz to 6 GHz	<8

LO Input/Export Connectors

LO OUT 1
IF2

Minimum RF power level	0 dBm
Nominal RF power level	+3 dBm
IF1	
Minimum RF power level	-12 dBm
Nominal RF power level	+5 dBm
LO IN 0	
IF2	
Minimum RF power level	0 dBm
Nominal RF power level	+2 dBm
Maximum RF power level	+20 dBm
IF1	
Minimum RF power level	-10 dBm
Nominal RF power level	-5 dBm
Maximum RF power level	+10 dBm
LO IN 1	
IF2	

Minimum RF power level	0 dBm
Nominal RF power level	+2 dBm
Maximum RF power level	+20 dBm
IF1	
Minimum RF power level	-10 dBm
Nominal RF power level	-5 dBm
Maximum RF power level	+10 dBm

Power



Caution The protection provided by this product may be impaired if it is used in a manner not described in this document.

Input voltage	9 V to 16 V, DC
Input current	7.5 A, maximum
Typical power consumption	38 W to 44 W, varies by application



Caution You must use an LPS or Class 2 power supply with the USRP-2945.

The power supply must also meet any safety and compliance requirements for the country of use.

Onboard DRAM

Memory size	1,024 MB
-------------	----------

Physical Characteristics

If you need to clean the module, wipe it with a dry towel.

Physical dimensions	
(L × W × H)	26.67 cm × 4.06 cm × 21.84 cm (10.5 in. × 1.6 in. × 8.6 in.)
Weight	1.588 kg (3.50 lb)

Environment

Ambient temperature range	0 °C to 55 °C (tested in accordance with IEC 60068-2-1 and IEC 60068-2-2)
Maximum altitude	2,000 m (800 mbar) (at 25 °C ambient temperature)
Pollution Degree	2

Indoor use only.

Operating Environment

Operating temperature	23 °C ± 5 °C, room temperature
Relative humidity range	10% to 90%, noncondensing (tested in accordance with IEC 60068-2-56)

Compliance and Certifications

Safety

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



Note For UL and other safety certifications, refer to the product label or the [Online Product Certification](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions
- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations, certifications, and additional information, refer to the [Online Product Certification](#) section.

CE Compliance

This product meets the essential requirements of applicable European Directives, as follows:

- 2014/35/EU; Low-Voltage Directive (safety)
- 2014/30/EU; Electromagnetic Compatibility Directive (EMC)

Online Product Certification

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for this product, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the ***Minimize Our Environmental Impact*** web page at ni.com/environment. This page contains the

environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)



EU Customers At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法（中国RoHS）



中国客户 National Instruments符合中国电子信息产品中限制使用某些有害物质指令(RoHS)。关于National Instruments中国RoHS合规性信息，请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)